

BOBO



glass origin





Bobo is smooth on the outside but when illuminated will display speckled patterns from tiny bubbles in the glass from a special blowing process by the Master artisan.

**Ordering Code**

Choose the desired light source, shade color, finish, from the options below.

example: 220 - 917 - mc




Light Source

-  **220** low voltage
-  **222** LED
-  **320** line voltage

Shade Colors

-  **909** clear
-  **915** blue
-  **917** red

Finish

-  **bz** bronze
-  **ch** chrome
-  **mc** matte chrome









Mounting Options

- MP** 4" Kiss Canopy
- MP2**** 2" Kiss Canopy

**2" Kiss not available for line voltage G9.



Technical Specs

<div>LOW</div> <div>system adaptor</div> <div>220-xxx</div>  <p>12V AC/DC input 50W, 5VA (max 50 Watt lamp) Dimmable</p> <p>Connects to UNI-LIGHT system Suitable for dry locations only</p>	<div>Kiss 4" Mono-Point Canopy</div> <div>220-xxx/MP</div>  <p>120VAC, 50/60Hz input 11.7V AC output 49W, 50VA (max 50 Watt lamp) Dimmable (Trailing Edge ELV)</p> <p>Mount to 3 1/2" - 4" round J-Box Suitable for dry locations only Short circuit protection Overload protection Thermal protection</p>	<div>Kiss 2" Mono-Point Canopy</div> <div>220-xxx/MP2</div>  <p>120VAC, 50/60Hz input 11.7V AC output 49W, 50VA (max 50 Watt lamp) Dimmable (Trailing Edge ELV) 2 1/4" hole cutout Required material thickness 3/16" - 1 1/16" Suitable for dry locations only Not thru-wire rated Short circuit protection Overload protection Thermal protection</p>
<div>LED</div> <div>system adaptor</div> <div>222-xxx</div>  <p>12V AC/DC input</p> <p>Connects to UNI-LIGHT system Suitable for dry locations only Compatible with dimmable power supply Compatible with selected Bruck electronic transformers and must meet the minimum VA (load)</p>	<div>Kiss 4" Mono-Point Canopy</div> <div>222-xxx/MP</div>  <p>100-277VAC, 50/60Hz input</p> <p>Mount to 3 1/2" - 4" round J-Box Suitable for dry locations only Short circuit protection Thermal protection</p>	<div>Kiss 2" Mono-Point Canopy</div> <div>222-xxx/MP2</div>  <p>100-240VAC, 50/60Hz input</p> <p>2 1/4" hole cutout Required material thickness 3/16" - 1 1/16" Suitable for dry locations only Not thru-wire rated Short circuit protection Overload protection Thermal protection</p>
<div>LINE</div> <div>system adaptor</div> <div>320-xxx</div>  <p>120VAC input 40W, 40VA (max 40 Watt lamp) G9 socket Dimmable (Incandescent)</p> <p>Connects to ZONYX system Suitable for dry locations only</p>	<div>Kiss 4" Mono-Point Canopy</div> <div>320-xxx/MP</div>  <p>120VAC input 40W, 40VA (max 40 Watt lamp) G9 socket Dimmable (Incandescent)</p> <p>Mount to 3 1/2" - 4" round J-Box Suitable for dry locations only</p>	

