



619.232.6064 | sales@urbanlighting.net | 301 4th Avenue | San Diego, CA 92101

KONCEPT






Lumens: Energy Consumption: Rated Lifespan: Color Temperature: CRI: Wall Switch (hardwired):


Dimmer: Brightness Adjustability: Standard Finishes:

300 5.5Watts 50,000 hours 2,700K 83

83
Compatible with any EIV wall dimmer and any 0-10V wall dimmer and any 0-10V wall dimmer.
Built-in touch dimmer switch Continuous Dimming Matte White, Silver, Chrome, Metallic Black, Oilled Walnut, White Gall, Matte Orange, Matte Red, Matte Fellow, Matte Pint, Matte Blue, Matte Green, Oxford Felt, Hongelder Sett, Aurer Felt Zinc alloy, plastic



Light source placed at 15" away from worksurface







Potential LEED Points:

Energy & Atmosphere (EA)

Credit 1.1: Optimize Energy Performance
LED lighting to reduce energy consumption.
(Potential points: 3)

(Neutral assists: 3)
Immoration in Design (In)
Copt 1.1. 3-4 Amoration in Design
Copt 1.1. 3-4 Amoration in Design
Copt 1.1. 3-4 Amoration in Design
The head swelse in all \$50 degrees giving the user full control in where
the light shines. Shine it up for ambient lighting, or down as a task light.
In ELD head can be descharded from the main body for easy warranty
service. The light can be controlled at its bead or by a wall dimmer. Also
the customizable surfaces would bring flexibility to users to create
own unique look. All these letes are very unique to Goray, additionally,
the head swelveing and detachable joint mechanism with no external
were significant approximation of the control of the control

All color finishes use water-based paint LEDs do not contain mercury

KONCEPT